

Fuse Disconnectors for 20 x 127mm Cylindrical Fuse Links CH127 Series



Catalogue Symbol:


CH127-1 (1-Pole) CH127-2 (2-Pole) CH127-3 (3-Pole) CH127-4* (4-Pole) CH127-5* (5-Pole)


Recommended Fuse Links: FWK, FWS, FWL, SRC750

Standards/Approvals:	IEC 60947-1 and 3, CE approval
Description:	Fuse disconnectors for 20 x 127mm cylindrical fuse links, which are suitable for protection of circuits up to 1000Vdc and 1500Vac.

Typical Applications: Photovoltaic systems, light rail and other traction applications.

Dimensions - mm





ø
0

Part Number	Number of Poles	Width - A (mm)
CH127-1	1-Pole	40
CH127-2	2-Pole	80
CH127-3	3-Pole	120
CH127-4*	4-Pole	160
CH127-5*	5-Pole	200

* Available on request

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

COOPER Bussmann

CHS Controls AB Florettgatan 33

chs@chscontrols.se www.chscontrols.se

SE-254 67 Helsingborg, Sweden Tel +46 42 38 61 00, Fax +46 42 38 61 29

Packaging:

Technical Data: Rated Voltage: Amps: Utilisation Category: Maximum Power loss per fuse link: Degree of protection: Connection: Weight:

MOQ: 1

1000Vdc/1500Vac 63A AC-20B, DC-20B

15W IP20 1 x 50mm² Cu both solid and stranded 1-Pole 0.48kg 2-Pole 0.96kg 3-Pole 1.44kg 4-Pole* 1.92kg 5-Pole* 2.4kg

controls