

## WeatherBox while-in-use weather protective covers

### Product description

- 1-Gang self-closing
- 2-Gang self-closing

### Design features

- Meets 2017 and 2020 NEC® 406.9 (B)(1) extra duty requirement for any application (WIU-1X, WIU-2X series only)
- Rugged UV-resistant polycarbonate cover and back protects devices without cracking or breaking and is non-corrosive and non-conductive
- Moveable hinges reposition easily for vertical or horizontal mounting (WIU-1 only)
- 1-Gang box includes 3 inserts for 16 different configurations
- 2-Gang box includes 4 inserts for over 60 different configurations
- Box inserts accommodate decorator devices, duplex receptacles, a variety of different single receptacle sizes and toggle switches
- Exceeds UL outdoor low voltage landscape lighting requirements
- Box cover includes pre-mounted gasket
- Meets Canadian Electrical Code rule 26-702



WIU-1



WIU-1D



WIU-2

### Standard depth

Gang	Description	# of available configurations	Color	Catalog no.
1-Gang	Horizontal/vertical mount	16	GY	<input type="checkbox"/> WIU-1
1-Gang	Horizontal/vertical mount	16	W	<input type="checkbox"/> WIU-1W
2-Gang	Horizontal/vertical mount	60+	GY	<input type="checkbox"/> WIU-2
2-Gang	Horizontal/vertical mount	60+	W	<input type="checkbox"/> WIU-2W

cULus Listed to UL514D, file no. E33216, certified to CSA C22.2 no. 42; meets NEMA 3R requirements

### Extra depth

Gang	Description	# of available configurations	Color	Catalog no.
1-Gang	Horizontal/vertical mount	16	GY	<input type="checkbox"/> WIU-1D

cULus Listed to UL514D, file no. E33216, certified to CSA C22.2 no. 42; meets NEMA 3R requirements

### Color ordering information:

Base device is gray. For white, add Color suffix: W (White)



**Compliances, specifications and availability are subject to change without notice.**